

CAUTION: The final determination as to the suitability of this product for any purpose is solely that of the user. Columbia products are not to be used to lift people or to lift anything over people.

### AC Electric Units

**HG3700-4A17-L-01**

H = Hoist  
 W = Winch  
 C = Capstan  
 T = Traction Drive

**Frame Size**  
 C/D = Frame 1  
 F = Frame 2  
 G = Frame 3

**Maximum rated capacity in lbs.** (does not apply to high speed units)

**Input Voltage**  
 1A = 115VAC  
 2A = 230VAC  
 4A = 460VAC

**Motor Speed**  
 17 = 1750 RPM  
 25 = 2500 RPM  
 34 = 3450 RPM

**Controls**  
 L = Low-voltage controls  
 F = Full-voltage controls  
 X = No controls

**Drum Size**  
 -01, -02, -03, -11 = Standard drum sizes  
 -00 = Custom drum configurations

### Pneumatic Units

**WD2000-P-01**

H = Hoist  
 W = Winch  
 C = Capstan  
 T = Traction Drive

**Frame Size**  
 C/D = Frame 1  
 F = Frame 2  
 G = Frame 3

**Maximum rated capacity in lbs.**

**Input Power**  
 P = Pneumatic

**Drum Size**  
 -01, -02, -03, -11 = Standard drum sizes  
 -00 = Custom drum configurations

Please note that all Columbia model numbers are for reference only. Specific performance information is available only with the product serial number.

Distributed by:

***ALLIED POWER PRODUCTS, INC.***

***THE WINCH & HOIST SPECIALISTS***

6590 SW Fallbrook Place, Beaverton, OR 97008

(503) 626-0654 Fax (503) 646-1996

[www.alliedpower.com](http://www.alliedpower.com)