



CAUTION: The final determination as to the suitability of this product for any purpose is solely that of the user. Columbia products are not to be used to lift people or to lift anything over people.

A strap drum option is offered for every standard Columbia Winch and Hoist model. With hoist capacities to 5,600 lbs. and winch capacities to 11,000 lbs., Columbia strap drum models provide versatile load handling capability while eliminating the inherent disadvantages of wire rope or chain.

In addition to being easier to handle, inspect and install, straps eliminate load rotation problems associated with wire rope and chain. Unlike wire rope, straps wind smoothly without long lead distances to the drum. Straps do not require lubrication nor do they "jagger", chip or spark.

Columbia winches and hoists are available with AC, DC, hydraulic and pneumatic motors to ensure their adaptability to any application. In addition to more than 400 standard models, specially adapted or custom designed strap winches and hoists are available to meet your exact requirements.

STANDARD MODELS

Frame 1

Hoist capacities to 2,700 lbs.
Winch capacities to 2,700 lbs.

Frame 2

Hoist capacities to 4,700 lbs.
Winch capacities to 7,000 lbs.

Frame 3

Hoist capacities to 5,600 lbs.
Winch capacities to 11,000 lbs.

For line pull and line speed performance, please refer to the appropriate Columbia Winch and Hoist technical specification sheet.

Distributed by:

ALLIED POWER PRODUCTS, INC.

THE WINCH & HOIST SPECIALISTS

6590 SW Fallbrook Place, Beaverton, OR 97008

(503) 626-0654 Fax (503) 646-1996

www.alliedpower.com